A&E Specifications

SHB-4300H Weather Proof Housing with Fully Cable Managed Bracket

Version 1.0

1. **GENERAL**
   a. All equipment and materials used shall be standard components that are regularly manufactured and used in the manufacturer's system.
   b. All systems and components shall have been thoroughly tested and proven in actual use.
   c. All systems and components shall be provided with an explicit manufacturer warranty.

2. **ELECTRICAL**

a. Input Voltage	24V AC
b. Power Consumption	Maximum 20W

3. **ENVIRONMENTAL**

a. Operating	
i. Temperature	-35°C - +50°C
On	5°C ± 5°C
ii. Blower	+45°C - +5°C

4. **MECHANICAL**

a. Dimensions :	147.2 x 107 x 422.4 mm (WxHxD) Outside 84 x 89 x 316 mm (WxHxD) Maximum Camera Lens combination)
b. Weight:	1.5Kg
c. Ingress Protection	IP66
d. Material	Die Casting ADC 12
e. Colour	Pantone Cool Gray 1C
f. Cable Glands	3 Separate Nylon Glands
g. Wall bracket	Comes with Fully Cable Managed Wall Bracket

5. **CERTIFICATIONS**

CE	EMC-Directive 2004 / 108 / EC
EMC Immunity:	EN 50130-4:2003
EMC Emissions	EN 50130-4:2003
FCC	Sub-part 15
UL	US, Canada

6. **WARRANTY** **3 years, parts and labour**